

Epson

TM-U295

Slip Printer



- Ultra-small footprint saves counter space
- Operator-friendly features
- Four print sizes, four printing directions
- “Page mode” feature allows printing anywhere on the document
- Compatible with Epson’s IntelliTrans™ family of transaction terminals
- Conforms with Epson’s ESC/POS®, the industry’s command set of choice
- Built-in Epson quality and reliability

Epson’s ultra-light, ultra-compact TM-U295 slip printer is just the right choice when space is limited. But, when it comes to versatility, this little printer is anything but limited.

With four print sizes, four print directions and a “page mode” that lets you print practically anywhere on the document, the TM-U295 offers all the options you need.

Quality that can be measured

Measuring just 180 x 190.5 x 101.5mm (W x D x H) {7.1 x 7.5 x 4.0"} and weighing only 1.6 kg (3.5 lbs), the TM-U295 is Epson’s smallest, most lightweight slip printer.

User-friendly features

The TM-U295 is loaded with user-friendly features, like its easy-to-use touch panel and automatic paper ejection, that make operation simple. The TM-U295 also has an Auto Status Back (ASB) function that automatically displays printer status, maximizing operator efficiency and productivity.

Ready for today and tomorrow

To save even more counter space, pair the TM-U295 with one of Epson’s IntelliTrans transaction terminals. This combination not only offers a much smaller footprint than standard POS systems, it also lets you choose from a much broader range of business applications. You can leverage your existing investment in the software you currently own. Either way, you’re assured that this printer will work for you today as well as tomorrow.

Epson quality and reliability

When you choose Epson’s TM-U295, you can be sure you’ll get unsurpassed performance and dependability. Because, like all Epson point-of-sale products, the TM-U295 meets Epson’s world-renowned standards for quality and reliability.

Epson **TM-U295** Slip Printer

Printer Specifications

General	Print method	7 pin, shuttle impact dot matrix
	Print font	
	Font	5 x 7/7 x 7
	Column capacity	35/42 columns
	Character size	1.6 x 2.9mm (W x H)/1.3 x 2.9mm (W x H); [0.063 x 0.114"/0.051 x 0.114"]
	Character set	95 Alphanumeric, 32 International, 128 x 3 Graphic
	Characters per inch	13.5 cpi/16.2 cpi
Printer	Interface	RS-232C, Bi-directional parallel
	Data buffer	512 bytes or 35 bytes
	Print speed	2.1 lps
	Paper dimensions	Slip: 80 to 182 x 69 to 257mm (W x L) {3.15 to 7.17 x 272 to 10.12"}
	Paper thickness	0.09 to 0.35mm [0.0035 to 0.0137"]
	Copy capability	One original and two copies
	Inked ribbon	ERC-27
	Ribbon life	1,000,000 characters
	Power	24 VDC ± 10%
	Power consumption	Approx. 600mA (at 24 VDC)
	D.K.D. function	2 drivers
	Reliability	
	MTBF	180,000 hours
	MCBF	7,000,000 lines
	Overall dimensions	180 x 190.5 x 101.5mm (W x D x H) {7.1" x 7.5" x 4.0"}
Mass	Approx. 1.6 kg [3.5 lbs]	
Control Board	EMI standards	VCCI class A, FCC class A, CE marking
	Safety standards	UL, CSA C22.2 No. 950

Inch values are approximate.

cpi: characters per 25.4mm (characters per inch)

lps: lines per second

