POINT-OF-SALE PRINTER Epson TM-T81





Epson's constant innovations in retail printing solutions give you the best performing printers to suit your business requirements and budget.

- The most durable and efficient thermal receipt printer Expected lifespan of 52 million lines (MCBF), 360,000 hours (MTBF) and auto-cutter life of 1.5million cuts
- More savings with minimal paper usage
 Adjustable margin settings reduce unnecessary paper wastage
- Easy installation and usage in any retail environment Windows Driver function makes the printer easy to install and use, and the wide angle of the top cover allows for quick roll replacement
- Specifically designed with safety in mind

 The circuit board is mounted upside down to protect it from accidental spillage





Epson TM-T81

SPECIFICATIONS		
EPSON is the registered trademark of Seiko Epson Corporation. All other product names and other company names used herein are for identification promotes on herein are the trademarks or registered trademarks of their respective owners. EPSON disclaims any and all rights in those marks. Scan/Print samples shown herein are simulations. Specifications are subject to change without notice.	PRODUCT CODE (INTERFACE)	C31C598202 - TM-T81-202 (Serial) C31C598204 - TM-T81-204 (Parallel) C31C598206 - TM-T81-206 (USB) C31C598208 - TM-T81-208 (Ethernet)
	PRINTER TYPE PRINTING METHOD DOT DENSITY PRINT DIRECTION PAPER WIDTH PRINTING WIDTH	Thermal Line Printing 203 dpi x 203 dpi [dpi: dots per inch (25.4 mm)] Unidirectional with friction deed 80 mm (3.15") 72 mm (2.83"), 576 dot positions
	PRINT FONTS CHARACTERS PER LINE (DEFAULT) CHARACTER SPACING (DEFAULT) LINE SPACING CHARACTER SET	48/64 0.25 mm (0.01") [2 dots] [Note: programmable by control demand] 3.75 mm (0.15") [Note: programmable by control demand] 95 Alphanumerical, 1 x International, 128 x 1 Extended Graphic South Asia models carry Thai (128 x 3) & Vietnamese (128 x 2) characters 12 x 24 / 9 x 17 / 9 x 24 (including 2-dot spacing horizontally)
	PRINTER SPEED NORMAL PAGE MODE PRINTING BIT-IMAGE PRINTING RASTER BIT-IMAGE PRINTING	150 mm/s (5.91"/s) Approx 40.0 lps [3.75 mm (0.15") feed] 150 mm/s (5.91"/s) 150 mm/s (5.91"/s) 150 mm/s (5.91"/s)
	LADDER BAR CODE, 2 DIMENSIONAL PRINTING PAPER FEED SPEED	99 mm/s (3.90"/s) Approx 150 mm/s (5.91"/s) [Continuous paper feeding]
	PAPER ROLL PAPER THICKNESS	Width: 79.5 ± 0.5 mm (3.13" ± 0.02") Diameter: 83 mm (3.27") maximum 0.06 to 0.07 mm (0.002" to 0.003")
	RELIABILITY MTBF (MEAN TIME BEFORE FAILURE) MCBF (MEAN CYCLE BEFORE FAILURE)	360,000 hours 52 million lines Auto cutter 1.5 million cuts
	DIMENSIONS	144 (W) x 189 (D) x 145 (H) mm 5.67" (W) x 7.44" (D) x 5.71" (H)
	WEIGHT	Approx. 1.7 kg
	CASE COLOUR	Dark Grey
	AUTOCUTTER	Built-in
	ROLL PAPER DEVICE	Built-in
	POWER	24VDC ± 7%
	POWER CONSUMPTION	Approx. 1.4 A (Mean)
	POWER SUPPLY	PS-180 (included)
	PRINTER DRIVER	Windows® Printer Driver (APD)

EPSON PHILIPPINES CORPORATION

8th Floor Anson's Centre 23 ADB Avenue, Ortigas Center Pasig City 1605, Philippines TEL: (+632) 706-2609 FAX: (+632) 706-2665

EPSON Customer Care: 1800-1069-37766 Website: http://customercare.epson.com.ph Email: customercare@epc.epson.com.ph Dealer's Stamp



Customer Care 1800-1069-37766