

CITIZEN

The desktop printer that makes life easy

Versatile desktop printer



Fast print speed

Printing a typical courier label takes just one second with virtually instant first label printing.

Durable internal power supply

All printers feature an internal mains power supply to provide the most reliable operation and avoid the problem of external power supplies.

Thermal Transfer

The CL-S621 is thermal transfer using a wide variety of ribbons to print on all media types.

CL-S621

Label, Desktop

Applications

- Courier
- E-Seller
- Healthcare
- Hospitality
- Logistics / Transport
- Manufacturing
- Pharmacy
- Retail
- SME / SMB



Desktop size - industrial performance.

TOMORROW'S PRINTING TODAY

Citizen Systems America Corporation, 363 Van Ness Way #404, Torrance, CA 90501, USA

CITIZEN SYSTEMS AMERICA CORPORATION

Specifications

Model	CL-S621
Printing Technology	Thermal Transfer + Direct Thermal
Resolution	203 dpi
Print Speed (maximum)	4 inches per second (100 mm/s)
Print Width (maximum)	4 inches (104 mm)
Media Width (min to max)	0.5 to 4 inches (12.5 to 118 mm)
Roll Size (max), Core Size	Inside diameter 5 inches (125 mm) External diameter 8 inches (200mm) Core size 1 inch (25mm)
Media Thickness (min to max)	63.5 to 254 µm
Media Length (min to max)	0.25 to 64 inches (6.35 to 1625.6 mm)
Media Sensor	Fully adjustable gap, notch and reflective black mark
Main Interface	Dual Interface Serial (RS-232C), USB (version 1.1)
Interface	Wireless LAN 802.11b and 802.11g standards, 100 metres, 64/128 bit WEP, WPA, up to 54Mbps, Ethernet (10/100 BaseT), Parallel (IEEE 1284 compliant)
Ribbon size	2.9 inches (74mm) maximum outside diameter. 360 meter length. 1 inch (25mm) core
Ribbon winding & type	Ink side in or out, switch selectable. Wax, Wax/Resin or Resin Type
Ribbon system	ARCP™ automatic ribbon tension adjustment
Mechanism	Hi-Lift™ metal mechanism with wide opening head
Control panel	4 buttons and 4 LEDs

CL-S621

Label, Desktop

Features & Benefits

- Hi-Open™ case for vertical opening, no increase in footprint and safe closing.
- No more unreadable labels - the ARCP™ ribbon control technology assures clear prints.
- Low space requirement - integrated power supply enables clean work station
- ENERGY STAR® compliant
- Recyclable packaging
- Basic peeler
- USB and Serial cables



All-metal mechanisms for strength and durability.

Model	CL-S621
Emulations (Languages)	Datamax® I-Class™ & DMX400™, Cross-Emulation™ - automatic switching between Zebra® ZPL-II® and Datamax® I-Class®, DMX400, Zebra® ZPL-II®, BASIC interpreter for data stream processing
Drivers and software	Free-of-charge on CD with printer, including support for various platforms
Flash (Non-Volatile Memory)	4 MB total, 1 MB available for user
Size (W x D x H) and Weight	231 x 289 x 270 mm, 4.5 Kg
Warranty	2 years on printer. 6 months or 50 Kms printhead

All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0